

AN161-2/RS

AC995-72-10

AN155-2/RS

26341-4L

Q6331-4



ASSEMBLE WITH 3 THREADS EXPOSED
AT ENDS OF TURNBUCKLE BARREL

(L)
④ CABLE #19 WIRE, TINNED CARBON ST'L,
NON FLEXIBLE - PRE-FORMED
SPEC AN KR-C-43.

NOTE:
1. PRE-STRETCH CABLE TO 60% OF RATED STRENGTH (1260) ①
2. CABLE TO BE COATED WITH 50% WHITE LEAD &
50% TALLOW SOLUTION

3 CADMIUM PLATE ALL STL PARTS
4 SWAGE ALL ENDS - SPEC 146

REPLACES

REPLACED BY

LIMIT ON DIMENSIONS
OTHERWISE SPECIFIED

$\pm \frac{1}{8}$

APPROVED 9.36
30

ITEM	QTY	DESCRIPTION	QTY	DESCRIPTION	QTY	DESCRIPTION
PBY-5	28L1040	2EA	PBY-5	28L1040	2EA	
PBY-3-4	28L1040	1	PBY-2	28L1040	1	
PBY-1	28L1040	1	PBY-1	28L1040	1	
XP3Y	28L1040	1	XP3Y	28L1040	1	
AN161-2/RS			AN161-2/RS			
AC995-72-10			AC995-72-10			
26341-4L			26341-4L			
Q6331-4			Q6331-4			
28L10394			28L10394			

LM RM PART NO LM RM
REQ REQ

PARTS LIST PER ASSY

5 Andrew Miller

35 2-8-37

CHECK ITEM

APP HAND

B 28L1039

6601782

CONSOLIDATED
AIRCRAFT CORP
BUFFALO, N.Y.

NOTED

1.0.1.2

CABLE - FLOAT -
LOCK. MECH. - ASSY